

# Magnetic Door Lock

## single Door 280kg

### VAC-MS280

#### MAGNETIC LOCK SERIES

Voltronics Magnetic Door Lock Single Door 280kg Uses advanced UK production and packaging technology, offering over 20% more holding force than similar products. The surface also meets UK antioxidant standards.



#### APPLICATION

---

Airports

Prisons

Warehouses

Subways

Intelligent buildings.

Commercial offices

Banks

Hospitals

Schools and universities

#### FEATURES

---

Heavy duty structure

Ultra Plus sensitive

Low consumption

High strength aluminum alloy materials

Pure copper magnetic coil

Silicon steel sheet main materials

NO/NC signal

Red/Green indicator

Delay adjustment

12/24v adjustable


# SPECIFICATIONS

Lock Size	170Lx35Wx21H(mm)
Armature plate	130Lx33Wx9.3H(mm)
Holding Force	280kg(350Lbs)
Voltage	DC12V or DC24V (adjustable)
Current Draw	12V/500mA 24V/250mA
Signal Output	Dry Contact, Max Rating of Contact Current 3A
Suitable for	Wooden, Glass,Metal, Fireproof door
Surface Temp	≤+20°C
Operating Temp	-10~+55°C(14-131F)
Suitable Humidity	0~90%(non-condensing)
Finishes for Shell	Anodized aluminium surface texture processing
Finishes for Magnetic	Zinc
Finishes for Armature	Zinc
Weight	1.1kg


## EM 125KHz Proximity Readers



**CP6-RX**  
Anti-vandal network reader EM, HID& Mifare



**CP002EM-M**  
Network reader



**CP1EM**  
Mini network reader




**CP002EM**  
Network reader




**CARDS 125K**  
Proximity cards


## MiFare 13.56MHz Proximity Readers




**CP6-RX**  
Anti-vandal network reader EM, HID& Mifare



**CP1MF**  
Mini network reader



**CP002MF**  
Network reader



**CARDS 13.5M**  
Proximity cards