

Stand Alone Reader

VAC-RS002

Waterproof Proximity

Access Control Stand alone
Water Proof IP68 single door
multifunction standalone access
controller or card reader.

FEATURES

- Very low power consumption
- Waterproof, conforms to IP68
- Easy to install
- Built in light display the working status



SPECIFICATIONS

Card type	NL
Waterproof degree	IP68
Environment Humidity	10% ~ 90%
Lock output	≤3A
Working voltage	DC12-24V ±10%
Static electricity	≤30mA
Alarm output	≤20A
Output short circuit protection time	100μS
Card read distance	2 ~ 5cm

SPECIFICATIONS

Ambient temperature	-45°C ~ 60°C
Door Opening Time	0 ~ 99s (Adjustable)
Metal structure design	anti-vandal Digital backlit keyboard.
All-in-one	WG26 output/input.
User capacity	2000 card user card, 2000 user password.
Access Way	card, password, card + password.
The doorbell button and interface	buttons and isolation circuit
Dimension	Connect to any external bell 120x56x20mm

EM 125KHz Proximity Readers

				
CP6-RX Anti-vandal network reader EM, HID & Mifare	CP002EM-M Network reader	CP1EM Mini network reader	CP002EM Network reader	CARDS 125K Proximity cards

MiFare 13.56MHz Proximity Readers

			
CP6-RX Anti-vandal network reader EM, HID & Mifare	CP1MF Mini network reader	CP002MF Network reader	CARDS 13.5M Proximity cards