

Magnetic Door Lock

Double Door 280kg

VAC-MS280D

MAGNETIC LOCK SERIES

Voltronics Magnetic Door Lock Double Door 280kg Uses advanced UK production and packaging technology, offering over 20% more holding force than similar products. The surface also meets UK antioxidant standards.



APPLICATION

Airports	Prisons	Warehouses
Subways	Intelligent buildings.	Commercial offices
Banks	Hospitals	Schools and universities

FEATURES

- Heavy duty structure
- Ultra Plus sensitive
- Low consumption
- High strength aluminum alloy materials
- Pure copper magnetic coil
- Silicon steel sheet main materials
- NO/NC signal
- Red/Green indicator
- Delay adjustment
- 12/24v adjustable

SPECIFICATIONS

Lock Size	500L*47W*26H(mm)
Armature plate	180L*38W*11H(mm)
Holding Force	280kg(600Lbs)*2
Voltage	DC12V or DC24V (adjustable)
Current Draw	12V/500mA 24V/250mA
Signal Output	Dry Contact, Max Rating of Contact Current 3A
Suitable for	Wooden door, Glass door, Metal door, Fireproof door
Surface Temp	≤+20°C
Operating Temp	-10~+55°C (14-131°F)
Suitable Humidity	0~90% (non-condensing)
Finishes for Shell	Anodized aluminium surface texture processing
Finishes for Magnetic	Zinc
Finishes for Armature	Zinc
Weight	4kg

EM 125KHz Proximity Readers



CP6-RX
Anti-vandal network reader EM, HID& Mifare



CP002EM-M
Network reader



CP1EM
Mini network reader



CP002EM
Network reader



CARDS 125K
Proximity cards

MiFare 13.56MHz Proximity Readers



CP6-RX
Anti-vandal network reader EM, HID& Mifare



CP1MF
Mini network reader



CP002MF
Network reader



CARDS 13.5M
Proximity cards